



Full Face Mask (F5A+)

family cares



Key Features



Loop-distributed dispersion vent holes

They help a lot to optimize the noise control and minimize the disturbance to your bed partner.



Liberty of vision

Based on the forehead frame-free design, users can embrace more vision with ease.



Groove-fit cushion

The auto adjustment on the nose bridge can be achieved easily by the groove-fit cushion.



Multiple sizes available

The cushion sizes L, M and S ensure wider user's range.

Technical Specifications

Pressure-Flow Curve	Flow Rate (L/min)	Mask Pressure (cmH ₂ O)
	Pressure (cmH ₂ O)	4 10 12 17 24 30
	Flow Rate(L/min)	22 37 41 49 59 67
Dead Space Information	Dead space is the empty volume of the mask up to the swivel. The dead space of the mask varies according to cushion sizes but is less than 225 ml.	
Therapy Pressure	4 to 30 cmH ₂ O	
Sound	DECLARED DUAL-NUMBER NOISE EMISSION VALUES in accordance with ISO 4871. The A-weighted sound power level of the mask is 25 dBA, with uncertainty 3 dBA. The A-weighted sound pressure level of the mask at a distance of 1 m is 17 dBA, with uncertainty 3 dBA.	

BMC Medical Co., Ltd.

Room 110, Tower A Fengyu Building, No.115 Fucheng Road, Haidian, 100036 Beijing, PEOPLE'S REPUBLIC OF CHINA
Tel: +86-10-5166 3880 / Fax: +86-10-5166 3880 ext. 810 / www.bmc-medical.com

V1.0 SC-A-202304025

Please contact us for more details, such as the available models and accessible market.