



# Nasal Pillows Interface (P6)

To rebuild your dream



# Nasal Pillows Interface (P6)

## Main Features




### Circular Dispersion Vent

The circular dispersion vent keep the noise as low as 18dB (A) and meanwhile protect your bed partner from being disturbed.

### All Size Kit

Three nasal pillow sizes, namely L, M and S, come in the package.




### Modular Main Frame

The main frame is compatible with all pillow sizes.

### Three-point-adjustable Headgear

The adjustable headgear is fit for most of the head sizes. Wider range, more inclusiveness.



# Nasal Pillows Interface (P6)

## Technical Specifications

Pressure-Flow Curve	<div><table><tr><td>Pressure (cmH<sub>2</sub>O)</td><td>4</td><td>8</td><td>10</td><td>12</td><td>16</td><td>18</td><td>20</td></tr><tr><td>Flow Rate (L/min)</td><td>17</td><td>25</td><td>28</td><td>31</td><td>37</td><td>40</td><td>42</td></tr></table></div>	Pressure (cmH <sub>2</sub> O)	4	8	10	12	16	18	20	Flow Rate (L/min)	17	25	28	31	37	40	42
Pressure (cmH <sub>2</sub> O)	4	8	10	12	16	18	20										
Flow Rate (L/min)	17	25	28	31	37	40	42										
Dead Space Information	Dead space is the empty volume of the nasal pillows and short tube assembly up to the swivel. The dead space of the P6 for Large pillows is 92 ml.																
Therapy Pressure	4 to 20 cmH <sub>2</sub> O.																
Resistance	Drop in Pressure measured (average for 3 sizes) at 50 L/min: 0.4 cmH <sub>2</sub> O at 100 L/min: 1.4 cmH <sub>2</sub> O																
Sound	DECLARED DUAL-NUMBER NOISE EMISSION VALUES in accordance with ISO 4871. The A-weighted sound power level of the mask is 26 dBA, with uncertainty 3 dBA. The A-weighted sound pressure level of the mask at a distance of 1 m is 18 dBA, with uncertainty 3 dBA.																

### BMC Medical Co., Ltd.

Room 110, Tower A Fengyu Building, No.115 Fucheng Road, Haidian, 100036 Beijing, PEOPLE'S REPUBLIC OF CHINA  
Tel: +86-10-5166 3880 / Fax: +86-10-5166 3880 ext. 810 / [en.bmc-medical.com](http://en.bmc-medical.com)

Not applicable to some markets, such as the U.S.

SC-A-202207004-V1.0